

# FUJIKURA CT08 SINGLE FIBRE CLEAVER



#### **PRODUCT OVERVIEW**

#### The CT08 is an incredibly robust and reliable optical fibre cleaver.

As a future-proofed cleaving solution created for easy integration into existing splicing processes, the CT08 has been designed for easy replacement of the fibre clamps and cleaver blade in the field, which reduces maintenance cost and saves time.

#### **Features & Benefits**

- Dedicated for single fibre cleaving.
- Fibre clamps and cleaving blade replaceable
- No tool necessary for blade rotation.
- Wide lever opening allows easy fibre placement.
- Simple, single-step operation.













Finish

Place fibre Cleave





## **Specification**

Model		CT08
Applicable optical fibre		Glass optical fibres
Number of fibres		Single
Cladding diameter		125μm
Coating diameter		160μm to 900μm (2mm/3mm cord & drop cable)
Cleaving length	AD-50	5mm to 20mm (coating diameter = 250μm) 10mm to 20mm (coating diameter > 250μm)
	FH-xx	10mm
Cleaving angle		Typical 0.5 degrees
Blade life		48,000 fibres (1,000 fibres x 3 heights x 16 positions)
Dimensions		110(W) x 95(D) x 45(H)mm
Weight		185g
Operation condition		Temperature: -10 to 50°C Humidity: 0 to 95% RH (Non-condensing)
Storage condition		Temperature: -40 to 80°C Humidity: 0 to 95% RH (Non-condensing)
Resistance feature*		Shock: 76cm (30") all direction drop
		Dust resistance: Exposure to dust (0.1 to 500µm dia. Alumina Silicate)
		Rain resistance: H=10mm/hr for 10min

 $<sup>^{\</sup>ast}$  Carried out in Fujikura labs in Japan. The shock resistance test do not guarantee the product will not be damaged under this conditions.

# **Standard Package**



# **Standard Items**

Description	Model No.	Qty
Main body	CT08	1pc
Fibre plate	AD-50	1pc
Spacer	SPA-CT08-10	1pc
Carrying case	CC-34	1pc
Hexagonal wrench	HEX-01	1pc
Instruction manual	M-CT08-EJ	1pc

## **Optional Items**

Description	Model No.
Blade	CB-07 (installed: 1pc)
Arm set	ARM-CT-08-01 (installed: 1pc)
Side cover	SC-CT08-01

## **Fibre Holders**

Description	Model No.
	FH-100-250 to 900
Applicable fibre holder	FH-50-250 / FH-50-900
7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	FH-60-250 / FH-60-900 FH-70-250 / FH-70-900

# **Optional Items**



Ver: EDPFUJCT080923.1