


40/4x10G ACTIVE OPTICAL CABLE

CQA-804A BREAKOUT TRANSCEIVER CABLE

PRODUCT OVERVIEW

Properties

- Multi-protocol support
- Data rate 4x 9.8 Gbps to 4x 11.3 Gbps
- QSFP+ to 4xSFP+
- Cable length from 0.5 to 50m
- Multimode Fibre
- Temperature Range 0 ... 70°C
- Power consumption <2.9 W
(<1.5 W for 40G terminal,
<0.35 W per 10G terminal)



General Data

Form Factor	QSFP+ to 4x SFP+
Cable Media Type	Active Optical Cable (AOC)
Media	MMF
Protocol	40G/10G Ethernet
Inbuilt FEC	No
Operation Temperature	0°C ... 70°C
Storage Temperature	-40°C ... 85°C
Power Consumption	<1.5 W
Digital Diagnostic Management (DDM)	Built-in
Laser Hazard Level	1
Available Cable Lengths	0.5m to 50m

Absolute Maximum Ratings

Maximum Supply Voltage Range	3.13 V ... 3.47 V
Maximum Storage Temperature Range	-40°C ... 85°C
Maximum Relative Humidity Range	5 % ... 85 %



Transmitter Specifications

Laser Type	VCSEL
Operating Wavelength Range	840 nm ... 860nm
Total Optical Output Power	< -2 dBm
Supported Data Rate	40 GbE

Receiver Specifications

Supported Data Rate	40 GbE
---------------------	--------

Order Code Explanation

CSA-804Axxxx-yyyy	"xxxx" is an alphanumeric string, describing the compatibility. "0000" means no special coding to ensure compatibility with a special switch type.	-yyyy: Numerical string, indicating the cable length in multiples of 0.1m.
-------------------	--	--

Ordering Information

Part Code	Item Description	Length in Metres
85240682	CQA-804A_0010	1
85240683	CQA-804A_0020	2
85240684	CQA-804A_0030	3
85240685	CQA-804A_0050	5

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

Ver: EDPHSCQA804A0624.1

Tel: 01376 510337 - E-mail: sales@edpeurope.com