

EZIBLANK® BLANKING PANELS

The use of blanking panels plays an important role in data centre airflow management, as they prevent hot server exhaust air from circulating back to the front of the rack and mixing with the cold air cooling the servers. EziBlank® blanking panels are available for 19", 21" and 23" racks.

The EziBlank® Range

EziBlank® 6RU 19" Blanking Panel, Black - P/N: 46-EZIBLANK



- 6RU Blanking panel that can be snapped at 1U intervals.
- Works with 19" EIA-310D compliant racks with square hole rails.
- Tool-less installation thanks to innovative 'pop-in' clip.
- Certified to ANS UL 94 V-0.
- Made from Acrylonitrile Butadiene Styrene (ABS).
- Panel Dimensions: 482mm x 267mm x 2mm.
- Supplied in pack of 10 panels.

EziBlank® 6RU 19" Blanking Panel, White - P/N: 46-EZIBLANK-W



- 6RU Blanking panel that can be snapped at 1U intervals.
- Works with 19" EIA-310D compliant racks with square hole rails.
- Tool-less installation thanks to innovative 'pop-in' clip.
- Certified to ANS UL 94 V-0.
- Made from Acrylonitrile Butadiene Styrene (ABS).
- Panel Dimensions: 482mm x 267mm x 2mm.
- Supplied in pack of 10 panels.

EziBlank® 6RU 19" Blanking Panel, Grey - P/N: 46-EZIBLANK-GREY



- 6RU Blanking panel that can be snapped at 1U intervals.
- Works with 19" EIA-310D compliant racks with square hole rails.
- Tool-less installation thanks to innovative 'pop-in' clip.
- Certified to ANS UL 94 V-0.
- Made from Acrylonitrile Butadiene Styrene (ABS).
- Panel Dimensions: 482mm x 267mm x 2mm.
- Supplied in pack of 10 panels.

EziBlank® 6RU Universal 19" Blanking Panel, Black - P/N: 46-EZIBLANK-UC



- 6RU Blanking panel that can be snapped at 1U intervals.
- Specially designed twist latches enable the panel to work with any EIA-310-D compliant 19" rack.
- Moulded stud aids positioning whilst twist latch secures the panel in place.
- Flame retardant ABS to UL-94 V0.
- Panel made from ABS with Ethylene Propylene Thermoplastic Elastomer (EPTR) twist latches.
- Panel Dimensions: 483mm x 270mm x 19mm.
- Supplied in pack of 10 panels.

EziBlank® 21" 10-SU Universal Blanking Panel, Black - P/N: 46-EZIBLANK-21



- 10-SU Blanking panel that can be snapped to various numbers of SU per panel.
- Installs using specially designed twist latches, 4 pairs per 10-SU panel. Additional latches available separately.
- Flame retardant ABS to UL-94 V0.
- Panel width is 495mm.
- Supplied in pack of 10 panels.

EziBlank® 6RU Universal 23" Blanking Panel, Black - P/N: 46-EZIBLANK-23



- 6RU Blanking panel that can be snapped at 1U intervals.
- Specially designed twist latches enable the panel to work with any EIA-310-D compliant 23" rack.
- Moulded stud aids positioning whilst twist latch secures the panel in place.
- Flame retardant ABS to UL-94 V0.
- Panel made from ABS with TER rubber twist latches.
- Panel Dimensions: 584mm x 270mm x 19mm.
- Supplied in pack of 10 panels.